

CLAIM AMENDMENTS

IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

1. (Original) A centrifuge for removing more dense material from a fluid medium, comprising:

a fluid separation wall placed within a sleeve to form a containment zone therebetween;

the containment zone operable to receive a portion of the fluid medium having a greater concentration of the more dense material;

the fluid separation wall aligned generally parallel to an axis of rotation and operable to rotate relative to the axis of rotation;

at least one receptacle forming a part of the fluid separation wall such that the at least one receptacle includes a void area;

the at least one receptacle operable to aid in separation of the more dense material from the fluid medium;

at least one opening extending through the fluid separation wall from the void area to the outer surface of the receptacle;

the at least one opening operable to transport the more dense material to the containment zone;

a valve ring forming a part of the fluid separation wall, the valve ring including at least one valve orifice formed in the valve ring; and

the valve ring having a first position which blocks the more dense material from exiting the receptacle and a second position that allows the more dense material to exit the fluid separation wall and move into the containment zone.

2. (Original) The centrifuge of Claim 1, wherein the fluid separation wall further comprises a plurality of the receptacles, each receptacle formed in the void area and having one or more respective openings.

3. (Cancelled).

4. (Original) The centrifuge of Claim 1, wherein the centrifuge comprises a split-cone centrifuge.

5. (Currently Amended) [The centrifuge of Claim 1, further comprising:] A centrifuge for removing more dense material from a fluid medium, comprising:

a fluid separation wall placed within a sleeve to form a containment zone therebetween;

the containment zone operable to receive a portion of the fluid medium having a greater concentration of the more dense material;

the fluid separation wall aligned generally parallel to an axis of rotation and operable to rotate relative to the axis of rotation;

at least one receptacle forming a part of the fluid separation wall such that the at least one receptacle includes a void area;

the at least one receptacle operable to aid in separation of the more dense material from the fluid medium;

at least one opening extending through the fluid separation wall from the void area to the outer surface of the receptacle;

the at least one opening operable to transport the more dense material to the containment zone;

a valve ring forming a part of the fluid separation wall, the valve ring including at least one valve orifice formed in the valve ring;

the valve ring having a first position which blocks the more dense material from exiting the receptacle and a second position that allows the more dense material to exit the fluid separation wall and move into the containment zone;

a pin operably engaged with the fluid separation wall, the pin extending radially from the fluid separation wall; and

a slot formed in the valve ring, the slot operably formed to receive the pin therethrough and to guide the valve ring between the first position and the second position such that a valve orifice aligns with the respective opening in the second position.

6. (Currently Amended) [The centrifuge of Claim 1, further comprising:] A centrifuge for removing more dense material from a fluid medium, comprising:

a fluid separation wall placed within a sleeve to form a containment zone therebetween;

the containment zone operable to receive a portion of the fluid medium having a greater concentration of the more dense material;

at least one receptacle forming a part of the fluid separation wall such that the at least one receptacle includes a void area;

the at least one receptacle operable to aid in separation of the more dense material from the fluid medium;

at least one opening extending through the fluid separation wall from the void area to the outer surface of the receptacle;

the at least one opening operable to transport the more dense material to the containment zone;

a valve ring forming a part of the fluid separation wall, the valve ring including at least one valve orifice formed in the valve ring;

the valve ring having a first position which blocks the more dense material from exiting the receptacle and a second position that allows the more dense material to exit the fluid separation wall and move into the containment zone;

a pin operably engaged with the valve ring, the pin extending radially through the valve ring to engage a slot; and

the slot formed in the fluid separation wall, the slot operably formed to receive the pin and to guide the valve ring between the first position and the second position such that a valve orifice aligns with the respective opening in the second position.

7. (Original) The centrifuge of Claim 6, wherein the slot comprises an oval shaped slot operably designed to restrict the movement of the valve ring.

8. (Original) The centrifuge of Claim 6, wherein the pin comprises a bolt.

9. (Original) The centrifuge of Claim 1, further comprising a detent or stop formed in the valve ring, the detent operable to maintain the valve ring in the first position.

10. (Currently Amended) [The centrifuge of Claim 1, further comprising:] A centrifuge for removing more dense material from a fluid medium, comprising:
a fluid separation wall placed within a sleeve to form a containment zone therebetween;
the containment zone operable to receive a portion of the fluid medium having a greater concentration of the more dense material;
the fluid separation wall aligned generally parallel to an axis of rotation and operable to rotate relative to the axis of rotation;
at least one receptacle forming a part of the fluid separation wall such that the at least one receptacle includes a void area;
the at least one receptacle operable to aid in separation of the more dense material from the fluid medium;
at least one opening extending through the fluid separation wall from the void area to the outer surface of the receptacle;
the at least one opening operable to transport the more dense material to the containment zone;
a valve ring forming a part of the fluid separation wall;
the valve ring having a first position which blocks the more dense material from exiting the receptacle and a second position that allows the more dense material to exit the fluid separation wall and move into the containment zone;
an upper wedge coupled to the fluid separation wall, the upper wedge operable to restrict the movement of the valve ring; and
a lower wedge coupled to the fluid separation wall, the lower wedge operable to restrict the movement of the valve ring.

11. (Original) The centrifuge of Claim 1, further comprising a pressure sensor operably coupled to the fluid separation wall, the pressure sensor operable to determine pressures within the fluid separation wall.

12. (Original) The centrifuge of Claim 1, further comprising an actuator operable to cause the valve ring to move between the first position and the second position.

13. (Original) The centrifuge of Claim 12, wherein the actuator comprises a brake pad and a solenoid operable to engage a portion of the valve ring to cause the valve ring to move between the first position and the second position.

14. (Original) The centrifuge of Claim 12, further comprising a controller operable to control the actuation of the actuator.

15. (Original) The centrifuge of Claim 1, further comprising at least one vane disposed on the valve ring, the at least one vane operable to interact with compressed air to cause the valve ring to move between the first position and the second position.

16. (Original) The centrifuge of Claim 1, further comprising a spring coupled between an outer section of the fluid separation wall and the valve ring, the spring operable to bias the valve ring toward the first position.

17. (Original) A centrifuge for removing more dense material from a fluid medium, comprising:

a fluid separation wall placed within a non-rotating sleeve to form a containment zone therebetween;

the containment zone operable to receive a portion of the fluid medium having a greater concentration of the more dense material;

the fluid separation wall aligned generally parallel to an axis of rotation and operable to rotate around the axis of rotation;

at least one receptacle forming a part of the fluid separation wall such that the at least one receptacle includes a void area, the at least one receptacle operable to aid in separation of the more dense material from the fluid medium;

at least one opening extending through the fluid separation wall from the void area to the outer surface of the receptacle;

the at least one opening operable to transport the more dense material to the containment zone;

a valve ring forming a part of the fluid separation wall, the valve ring including at least one valve orifice formed in the valve ring;

the valve ring aligned perpendicular to the axis of rotation and operable to slide along the fluid separation wall to move between open and closed positions; and

the at least one valve orifice operable to align with the at least one opening such that the more dense material exits the fluid separation wall and moves into the containment zone.

18. (Original) The centrifuge of Claim 17, further comprising a wear insert nozzle disposed in the opening, the wear insert nozzle operable to seat against the valve ring and guide the more dense material from the receptacle to the containment zone.

19. (Original) The centrifuge of Claim 18, wherein the size of the orifice is smaller than the size of the wear insert nozzle.

20. (Original) The centrifuge of Claim 18, wherein the wear insert nozzle comprise replaceable wear insert nozzles.

21-33. (Withdrawn)

34. (Original) A fluid separation wall for separating more dense material from a fluid medium in a centrifuge, comprising:

a generally circular wall formed around an axis of rotation with an inner surface and an outer surface such that the outer surface is further from the axis of rotation than the inner surface;

the wall including at least one receptacle, the wall operable to receive a fluid medium having more dense material;

an opening formed in the wall, the opening extending from the at least one receptacle through the wall from the inner surface to the outer surface; and

a valve ring having at least one orifice and formed over the opening, the valve ring operable to slide along the outer surface of the wall such that the at least one orifice aligns with the opening.

35. (Currently Amended) [The fluid separation wall of Claim 34, further comprising:] A fluid separation wall for separating more dense material from a fluid medium in a centrifuge, comprising:

a generally circular wall formed around an axis of rotation with an inner surface and an outer surface such that the outer surface is further from the axis of rotation than the inner surface;

the wall including at least one receptacle, the wall operable to receive a fluid medium having more dense material;

an opening formed in the wall, the opening extending from the at least one receptacle through the wall from the inner surface to the outer surface;

a valve ring having at least one orifice and formed over the opening, the valve ring operable to slide along the outer surface of the wall such that the at least one orifice aligns with the opening;

an upper wedge coupled to the outer surface of the wall, the upper wedge operable to restrict the movement of the valve ring; and

a lower wedge coupled to the outer surface of the wall, the lower wedge operable to restrict the movement of the valve ring.

36. (Original) The fluid separation wall of Claim 34, further comprising a pressure sensor operably coupled to the fluid separation wall, the pressure sensor operable to determine the pressure of with the fluid separation wall.

37. (Original) The fluid separation wall of Claim 34, further comprising an actuator operable to cause the valve ring to slide between open and closed positions.

38. (Original) The fluid separation wall of Claim 34, further comprising a controller operable to control the actuation of an actuator.

39. (Original) The fluid separation wall of claim 34, further comprising a slot and pin operable to guide the valve ring between a first and second position such that the at least one orifice aligns with the respective opening.

40. (Original) The fluid separation wall of Claim 34, further comprising a plurality of vanes disposed on the valve ring, the vanes operable to interact with compressed air to cause the valve ring to move between open and closed positions.

41. (Original) The fluid separation wall of Claim 34, further comprising a spring coupled between an outer section of the wall and the valve ring, the spring operable to bias the position of the valve ring.

42. (Original) The fluid separation wall of Claim 34, further comprising a wear insert nozzle disposed in the opening, the wear insert nozzle operable to seat against the valve ring and guide the more dense material from the receptacle to the containment zone.